



**AIR MOVEMENT AND CONTROL
ASSOCIATION INTERNATIONAL, INC.**

30 West University Drive
Arlington Heights, IL 60004-1893 U.S.A.
Tel: (847) 394-0150 • Fax: (847) 253-0088
E-Mail : info@amca.org • Web: www.amca.org

CHECKLIST: DAMPER CATALOGS

CATALOG IDENTIFICATION _____ DATE OF CATALOG _____

I. SEAL USAGE IN CATALOGS

A. Pick the Correct Seal: [check all that apply]

- Air Performance
- Air Leakage and Air Performance

B. Placement of Seal: [check all that apply]

- 1. If the catalog contains all licensed products, the seal and qualifying statement shall be prominently displayed either on the cover or in the catalog.
- 2. If the catalog contains both licensed and unlicensed products, the seal and qualifying statement shall not be shown on the outside cover.
- 3. In addition, the seal may be shown on any page with licensed performance data.

C. Reproduction of Seal

- 1. Size: No reproduction of the AMCA International Certified Ratings Seal in published material shall be larger than 42 mm x 70 mm (1 5/8 inches x 2 3/4 in.), unless the AMCA International staff gives specific permission.
- 2. Color: When using one color reproduction, black is preferred. If light colored paper is used, regard it as white for this purpose. The full color AMCA Seal may be used. The CRP Manager will email reproductions of the seal for use in the catalog upon request.

D. Member Logo

- Other than the AMCA International Certified Ratings Seal, no logo or mark incorporating the acronym AMCA International or initials A.M.C.A. such as the member logo shall be reproduced in any catalog or publication containing performance ratings of any kind.

II. QUALIFYING STATEMENT ADJACENT TO THE SEAL

- In catalogs containing ratings of licensed products, the following statement shall be printed prominently and immediately adjacent to the reproduction of the AMCA Certified Ratings Seal:

(Licensee's name as shown on License Agreement) certifies that the (product description) shown herein is (or are) licensed to bear the AMCA Seal. The ratings shown are based on tests and procedures performed in accordance with AMCA Publication 511 and comply with the requirements of the AMCA Certified Ratings Program.



**AIR MOVEMENT AND CONTROL
ASSOCIATION INTERNATIONAL, INC.**

30 West University Drive
Arlington Heights, IL 60004-1893 U.S.A.
Tel: (847) 394-0150 • Fax: (847) 253-0088
E-Mail : info@amca.org • Web: www.amca.org

III. CATALOG IDENTIFICATION REQUIREMENTS

- Catalogs containing performance ratings of licensed products shall be provided with a catalog identification reference, and the month and year of publication shall be spelled out, e.g. "November 2004," on the outside front or outside back cover of the product catalog.
- The catalog identification may be any combination of letters and/or numbers. Where ratings are on separate sheets or on loose leaf that may be removed from the cover, each sheet or loose leaf shall be identified and dated as above. The final printed catalog shall have a current date.

IV. REQUIRED STATEMENTS

A. Statement Following the Qualifying Statement

- Immediately following the seal and qualifying statement there should be statement identifying the type of performance that is licensed. The sentence should say "The AMCA Certified Ratings Seal applies to XXXXX only." As an example "The AMCA Certified Ratings Seal applies to air performance ratings only." or "The AMCA Certified Ratings Seal applies to air performance and air leakage ratings only."

B. Air Leakage Statement

- Published air leakage data shall state that air leakage is based on operation between 10°C – 40°C (50°F – 104°F).

V. ADDITIONAL REQUIREMENTS

A. Air Leakage Ratings

- The method of torque or force calculation shall be clearly identified in the published data.

B. Rectangular Dampers

- Classes for the following sizes only shall be published for air leakage:

12 in X 12 in.	12 in. X 48 in
24 in. X 24 in.	48 in. X 12 in.
36 in. X 36 in.	Max. width X 36 in. height
- Data for the following sizes only shall be published for air performance:

12 in. X 48 in.	36 in. X 36 in.
12 in. X 12 in.	48 in. X 12 in.
24 in. X 24 in.	



**AIR MOVEMENT AND CONTROL
ASSOCIATION INTERNATIONAL, INC.**

30 West University Drive
Arlington Heights, IL 60004-1893 U.S.A.
Tel: (847) 394-0150 • Fax: (847) 253-0088
E-Mail : info@amca.org • Web: www.amca.org

C. Round Dampers

- Classes for the following sizes only shall be published for air leakage:

Minimum size damper
Maximum size damper

- Data for the following sizes only shall be published for air performance:

12 in.
24 in.
36 in.

D. Backdraft Dampers

- Data for the following sizes only shall be published for air leakage:

Minimum width – maximum height
Maximum width – minimum height
Maximum width – maximum height

Opt. For air performance test and publish sizes listed in Section B.

VI. MISCELLANEOUS ITEMS FOR ALL CATALOGS

- Where the ratings of licensed products are on the same page or "spread" as nonlicensed products, a clear physical separation and statement shall differentiate licensed products from nonlicensed products.

- The use of asterisks or similar marks to distinguish licensed products from nonlicensed products is unacceptable.

- In connection with nonlicensed products, the use of any phrase that is liable to be misinterpreted to mean that such products are licensed to use the AMCA International Certified Ratings Seal shall be prohibited. Phrases such as "tested and rated to AMCA International standards" or "rated to AMCA International standards" shall not be used.

- There shall be no unauthorized use of AMCA International copyrighted material. See the AMCA International website for the policy on using AMCA copyrighted material.